

## AlertBuddy Deaf Persons Alert Kit

Part No. **BF325/K1**



### Overview

- A moveable deaf persons fire alarm alert system ideal for use at home, in hotel bedrooms and other residential settings.
- Works by monitoring and listening to the ambient sound in a room and automatically detecting the presence of a fire alarm signal.
- When a fire signal is detected, Alert Buddy will flash, emit a <1KHz low frequency tone (75dBa @ 1m) and activate a vibrating pillow pad (supplied).
- The combination of light + sound + vibration helps maximise the chances of someone being alerted to a fire alarm even if they are sleeping.
- The AlertBuddy unit can be wall mounted or will sit on top of a table.
- Includes a BF325 AlertBuddy unit with combined Silence / Test button, and BF320 vibrating pillow pad.
- Visual Alarm Indicator designed to the O Class requirements of EN54-23.
- Complies with BS 5446-3 requirements.
- Plugtop charger/adaptor supplied.

### Technical Specifications

|                                  |                                                                                                           |
|----------------------------------|-----------------------------------------------------------------------------------------------------------|
| Approvals/certifications         | Complies with BS 5446-3 requirements.                                                                     |
| Supply/operating voltage         | 20V                                                                                                       |
| Mains supply                     | The kit is supplied with a 230Vac plugtop charger.                                                        |
| Max battery size and type        | Li-Ion 3.7v rechargeable standby battery.                                                                 |
| Product dimensions (mm)          | AlertBuddy = 206(L) x 108(W) x 61(H)mm; Vibrating Pillow Pad = 100m diameter x 34(D)mm; lead measures 2m. |
| Construction & finish            | White moulded polycarbonate.                                                                              |
| Weight                           | 470g (AlertBuddy unit); 260g (portable pillow pad).                                                       |
| Operating conditions/temperature | -5°C to +40°C.                                                                                            |