



# PL 60

HIGH EFFICIENCY CEILING SPEAKER



## Description

The PL60 is a ceiling speaker with an elegant design, intended for recess installation in false ceilings or panels. It is ideal for the reproduction of announcements and background music and features a multiplesocket line transformer for use with constant voltage systems.

## Features

- › 6" fullrange transducer
- › Power selectable (70 V / 100 V): 6 W – 3 W – 1.5 W
- › 91 dB sensitivity
- › Colour white RAL 9003
- › Plastic frame, steel grille

## Part Number

13110214 PL 60



White - RAL 9003 EAN 8024530010102



# PL 60

## HIGH EFFICENCY CEILING SPEAKER

Line Art 2D



### TECHNICAL SPECIFICATIONS

<b>Acoustical specifications</b>	Frequency Response (-10dB)	90 Hz - 20000 Hz
	Max SPL @ 1m	107 dB
	Coverage angle	90°
	System Sensitivity	91 dB
<b>Power section</b>	Amplification	Full Range
	Nominal Impedance	8 ohm
	Power Handling	6 W
	Peak Power Handling	24 W PEAK
	Recommended Amplifiers	DMA 504, DMA 162, DMA 82, DMA 162P, ES 2160, ES 3080, AM 2320, AM 2160, AM 2080, AM 1125, UP 8504, UP 8502, UP 8501, UP 2321, UP 2162
<b>Transducers</b>	Fullrange	1 x 6.0"
<b>Input/Output section</b>	Input connectors	Screw Terminals
	Output connectors	Screw Terminals
	Constant Voltage Transformer	70/100 V
	Power selection 1	6 W - 1667 ohm
	Power selection 2	3 W - 3333 ohm
	Power selection 3	1.5 W - 6667 ohm
<b>Standard compliance</b>	Safety agency	CE compliant
<b>Physical specifications</b>	Cabinet/Case Material	Plastic
	Hardware	Plastic Material
	Grille	Steel
	Color	White - RAL 9003



# PL 60

## HIGH EFFICENCY CEILING SPEAKER

### Size / Weight

Depth	75 mm / 2.95 inches
Recessed Depth	69 mm / 2.72 inches
Diameter	204 mm / 8.03 inches
Weight	0.34 kg / 0.75 lbs

### Rigging / Mounting

#### ACCESSORIES

##### INSTALLATION PLATES

13320107    A 1360

White - RAL 9003 EAN 8024530015794