

STRIKE Saber 10

FEATURES

- Intense fully IP65 10-cell batten perfect as a blinder, footlight, or tunable warm-white wash
- Emulated “red shift” to mimic incandescent fixtures perfectly.
- 16-bit dimming control for smooth, perfect fades
- Strobe functionality for high-impact effects on-the-fly
- Pixel mappable for intense chase and strobe effects
- End to end easy rigging.
- NFC Chip in built
- Easy to use OLED display
- Adjustable Pulse Width Modulation (PWM)
- RDM (Remote Device Management) for added flexibility



SPECIFICATIONS

OPTICAL

- 10 LEDs (Warm White/Amber)
- Color Temperature (at full): 2792 K
- CRI: 92.9
- TLCI: 91
- Beam Angle vertical: 20.9
- Beam Angle horizontal: 20.9
- Field Angle vertical: 25.1
- Field Angle horizontal: 25.1
- Lumens: 5,959
- Illuminance: 1686 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Strobe: Electronic
- Strobe Rate: 0 to 26.7 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Dimensions: 39.3 x 3.08 x 6.18 in (1000 x 78.4 x 157 mm)
- Weight: 14.6 lb. (8 kg)
- Exterior Color: Black
- Housing Material: Aluminum alloy, Aluminum die-cast

CONNECTIONS

- Power Connection: Edison (Local) plug to Seetronic Tru1
- Power Input Seetronic Tru1
- Power Output: Seetronic Tru1

- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

CONTROL

- Control Protocol: DMX, RDM
- DMX Channels: 1, 3, 6, 13, 22, 26Ch1 or 26Ch2
- Modes/Personalities: 6 personalities (1Ch, 3Ch, 6Ch, 13Ch, 22Ch, 26Ch1, 26Ch2)

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 6 units @ 110 V; 16 units @ 208 V; 1 units @ 230 V
- Power and Current: 183 W, 1.83 A @ 100 V, 60 Hz
- Power and Current: 181 W, 1.52 A @ 120 V, 60 Hz
- Power and Current: 178 W, .86 A @ 208 V, 60 Hz
- Power and Current: 177 W, .78 A @ 230 V, 50 Hz
- Power and Current: 178 W, .75 A @ 240 V, 60 Hz

CERTIFICATIONS / QUALIFICATIONS

- CE, MET
- IP Rating: IP65
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

WHAT'S INCLUDED

- STRIKE Saber
- Seetronic Powerkon – Bare Wire

OPTIONAL ACCESSORIES

- Professional Clamps: CTC-50HC, CTC-50HCN
- Seetronic Powerkon power linking cables
- 5-pin DMX Cables