



# SUB 18-AS

PROFESSIONAL ACTIVE SUBWOOFER




<b>Description</b>	<p>The SUB 18-AS is a portable 18" high-power active subwoofer for live sound applications. It features a state-of-the-art transducer and a powerful 2200 Watts Class-D amplifier that delivers sound pressure levels up to 135 dB with exceptional headroom. Designed as the ideal complement for 10", 12" or 15" loudspeakers, it includes Bass Motion Control algorithm for extended bass response at any volume. The connection panel features mono/stereo Combo inputs, an XLR stereo link, and XLR crossover outputs. Rear panel controls include volume, polarity, and low-pass frequency selection. The rugged all-wood cabinet with scratch-resistant polyurea coating makes it durable, easy to carry and install securely. With its versatility, sound quality, and high power output, the SUB 18-AS is perfect for small to mid-sized venues and portable applications.</p>								
<b>Features</b>	<ul style="list-style-type: none"><li>› 2200Watt</li><li>› 135 dB max SPL</li><li>› 35 Hz - 400 Hz frequency response</li><li>› 18" Woofer, 4.0" voice coil</li><li>› Birch tour grade cabinet with polyurea coating</li><li>› Mono/Stereo XLR/TRS combo In + Link, Stereo XLR Xover Out</li><li>› Volume, polarity, and lowpass frequency selection</li></ul>								
<b>Part Number</b>	<table><tr><td>13000787 SUB 18-AS</td><td>220-240 V</td><td>Black</td><td>EAN 8024530021832</td></tr><tr><td>13000788 SUB 18-AS</td><td>100-120 V</td><td>Black</td><td>EAN 8024530021863</td></tr></table>	13000787 SUB 18-AS	220-240 V	Black	EAN 8024530021832	13000788 SUB 18-AS	100-120 V	Black	EAN 8024530021863
13000787 SUB 18-AS	220-240 V	Black	EAN 8024530021832						
13000788 SUB 18-AS	100-120 V	Black	EAN 8024530021863						



# SUB 18-AS

PROFESSIONAL ACTIVE SUBWOOFER

Line Art 2D



## TECHNICAL SPECIFICATIONS

<b>Acoustical specifications</b>	Frequency Response	35 Hz - 400 Hz
	Max SPL @ 1m	135 dB
<b>Transducers</b>	Woofer	1 x 18", 4.0" v.c
<b>Input/Output section</b>	Input signal	bal/unbal
	Input connectors	Combo XLR/Jack
	Output connectors	XLR
	Input sensitivity	-2 dBu/+4 dBu
<b>Processor section</b>	Protections	Thermal
	Limiter	Soft Limiter
	Controls	Volume, Polarity, Low pass filter frequency
<b>Power section</b>	Total Power	2200 W Peak
	Cooling	Convection
	Connections	VDE
<b>Standard compliance</b>	Safety agency	CE compliant
<b>Physical specifications</b>	Cabinet/Case Material	Baltic birch plywood
	Handles	2 side
	Pole mount/Cap	M20 thread
	Grille	Steel
	Color	Black
<b>Size / Weight</b>	Height	693 mm / 27.28 inches
	Width	505 mm / 19.88 inches
	Depth	685 mm / 26.97 inches
	Weight	44.5 kg / 98.11 lbs



# SUB 18-AS

PROFESSIONAL ACTIVE SUBWOOFER

<b>ACCESSORIES</b>				
Rigging / Mounting	<b>POLE MOUNT KITS</b>	13360067	PM-KIT M20	Black EAN 8024530014599
Protections	<b>BAGS, COVERS</b>	13360530	CVR 003	Black EAN 8024530020422
Transportation	<b>WHEELS</b>	13360238	WH PRO 4X	EAN 8024530018320